

KEY FEATURES

- Excellent 3 way system for rear desk application
- Good power handling (100 w RMS / 200 w maximum)
- Extended frequency range (50-20000 Hz)
- Excellent sensitivity (94 dB)
- Paper cone on woofer and middle range units
- Aluminium tweeter diaphragm

WOOFER SPECIFICATIONS

Nominal diameter	250 mm. 10 in.
Nominal impedance	4 ohms
Power handling / maximum	100 W RMS / 200 W
Sensitivity	95 dB 1w @ 1m
Frequency range	60 - 6000 Hz
Resonant frequency, fs	57 Hz
D.C. voice coil resistance, Re	3.9 ohms.
Mechanical quality factor, Qms	3.47
Electrical quality factor, Qes	0.39
Total quality factor, Qts	0.35
Equivalent air volume to Cms, Vas	44 l.
Efficiency, ηo (%)	2.1
Effective surface area, Sd	380 cm ²
Xmax	3 mm



MID FREQ DRIVER SPECIFICATIONS

Nominal diameter	130 mm. 5.25 in.
Nominal impedance	4 ohms
Power handling / maximum	30 W RMS / 60 W
Sensitivity	87 dB 1w @ 1m
Frequency range	85 - 12500 Hz

TWEETER SPECIFICATIONS

Nominal impedance	4 ohms
Power handling / maximum	25 W RMS / 50 W
Sensitivity	94 dB 1w @ 1m
Frequency range	1 - 16 kHz


FILTER SPECIFICATIONS

Power handling	150 W RMS
Crossover frequency	0.9 - 5 kHz
Attenuation slope	6 - 12 dB/oct.
H.F. attenuation	-3 dB, -6 dB

MOUNTING INFORMATION

Woofer baffle cutout diameter	233 mm. 9.17 in.
Woofer mounting depth	103 mm. 4.06 in.
Mid range unit cutout diameter	113 mm. 4.45 in.
Mid range unit mounting depth	55 mm. 2.17 in.
Tweeter baffle cutout diameter	94 mm. 3.70 in.
Tweeter mounting depth	39 mm. 1.54 in.
Filter external dimensions	144 x 104 x 51 mm. 5.67 x 4.09 x 2 in.

FREQUENCY RESPONSE



Note: on axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1w @ 1m.



E.B. ACOUSTIC & ELECTRONIC RESEARCH S.R.L.

Via S. Bartolomeo, 10 - 28047 OLEGGIO (NO) Italy Ph. 0039 0321 91430 - Fax 0039 0321 94411

www.ebacoustic.it