

COAXIAL

My 69X

- 1 Surround in gomma.
- 2 Gasket in ABS per iniezione.
- 3 Cono in FIBREGLASS.
- 4 Trecciole argentate.
- 5 Tweeter al neodimio.
- 6 Terminali 4,8x7,2 mm.
- 7 Cestello a norme DIN in lamiera con trattamento texture anti-corrosivo.

Frequency range	80 - 20000	Hz
Equivalent volume, Vas	11.944	L
Compliance, Cms	0.0020	mm/N
Mechanical resistance, Rms	3.6	Ns/m
Effective diaphragm/cone area, Sd	205	cm ²
Voice coil diameter	30.5	mm
Voice coil height	8	mm
Air gap height	4.5	mm
Linear excursion, Xmax	± 1.75	mm
Max mechanical excursion	± 9	mm
Nominal impedance	4	ohm
Voice coil resistance	4.29	ohm
Voice coil inductance	0.24	mH
Free air resonance, Fs	80.18	Hz
Sensitivity, Spl (2.83V/1m)	94.0	dB
Force factor, Bxl	5.300	Tm
Moving mass, Md	19.688	g
Qms	4.040	
Qes	1.514	
Qts	1.102	
Nominal power	80	W
Short term max power	320	W
Long term max power	160	W

