

# COAXIAL

# TG 6X

- 1 Surround in gomma.
- 2 Gasket in ABS per iniezione.
- 3 Cono Silver in cellulosa trattata.
- 4 Treccie argentate.
- 5 Tweeter al neodimio.
- 6 Terminali placcati oro 4,8x7,2 mm.
- 7 Cestello a norme DIN in lamiera con trattamento texture anti-corrosivo.

Frequency range	75 - 20000 Hz
Equivalent volume, Vas	0,001/10 Lt
Compliance, Cms	0,04/0,40 mm/N
Effective diaphragm/cone area, Sd	4,09/133 cm <sup>2</sup>
Voice coil diameter	13/25 mm
Voice coil height	1,05/10 mm
Air gap height	2/4 mm
Linear excursion, Xmax	± -/3 mm
Max mechanical excursion	± -/4 mm
Nominal impedance	4/4 ohm
Voice coil resistance	3,1/3,55 ohm
Voice coil inductance	0,03/0,58 mH
Free air resonance, Fs	2000/72 Hz
Sensitivity, Spl (2.83V/1m)	89/90 dB
Force factor, Bxl	-/4,63 Tm
Moving mass, Md	0,2/11,24 g
Qms	-/3,44
Qes	-/0,91
Qts	-/0,72
Nominal power	60 W
Short term max power	240 W
Long term max power	120 W

